



MOTO COMPETICION 2T

■ Description

Suitable for competition and for daily use, Repsol Moto Competición 2T is a synthetic lubricant oil which is formulated to provide total engine protection and immediate acceleration. Moreover, it is especially suitable for low contaminating emission engines; its composition prevents the formation of deposits in the exhaust system, which prolongs its life and engine life. It is suitable for engines with a premix in the fuel and also for those that use an injector lubrication system.

■ Properties

- Formulated to provide total protection, excellent for ensuring a clean engine and low emissions.
- Its components prevent the formation of deposits, helping to keep the exhaust ports clean.
- It extends the engine's lifespan, preventing any sticking of the piston rings, sweating of spark plugs and the formation of carbonous residues.
- It minimises the emission of fumes, contributing to a reduction in pollution.

■ Quality level

- JASO M345 FD (Code 034RYL001)
- ISO-L-EGD
- API TC
- TISI
- Aprilia DFI

■ Technical Characteristics

	UNIT	METHOD	VALUE
Density at 15°C	g/cm ³	ASTM D 4052	0.870
Viscosity at 100°C	cSt	ASTM D 445	9
Viscosity at 40°C	cSt	ASTM D 445	56
Viscosity rate	-	ASTM D 2270	140
Flash point, open cup	°C	ASTM D 92	130
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% in weight	ASTM D 874	0.1

■ Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

■ Handling

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

■ Health and safety hazards

Inhalation: Given that it is not a particularly volatile product, the risk of inhalation is minimal.

Ingestion: Do not induce vomiting. Supply water. Seek medical advice.

Contact with the skin: Wash thoroughly with soap and water.

Eyes: Wash thoroughly with water.

General measures: Seek medical advice.

■ Fire-extinguishing measures

No special measures required.

Fire-extinguishing measures: Foams, dry chemicals, CO₂, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

■ Environmental precautions

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

repsolypf.com

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.