



MOTO OFF ROAD 2T

■ Description

Synthetic lubricant oil for very high performance 2-stroke engines; it is mainly suitable for all top-level off-road specialities. This product has been conscientiously designed to ensure maximum engine protection against wear in the extreme conditions to which this type of motorbike is subjected. It is suitable for both premix and for injector lubrication systems.

■ Properties

- Specially developed for use in conditions of high rotations, demonstrating superior capacity in off-road use.
- Excellent protection against wear and improved engine cleanliness guaranteed in conditions of extreme use.
- Its components prevent the formation of deposits, helping to keep the exhaust ports clean.
- It extends the engine's lifespan, preventing any sticking of the piston rings, sweating of spark plugs and the formation of carbonous residues.

■ Quality level

- JASO M345 FD (Code 034RYL002)
- ISO-L-EGD
- API TC
- TISI
- Aprilia DFI

■ Technical Characteristics

	UNIT	METHOD	VALUE
Density at 15°C	g/cm ³	ASTM D 4052	0.872
Viscosity at 100°C	cSt	ASTM D 445	10
Viscosity at 40°C	cSt	ASTM D 445	64
Viscosity rate	-	ASTM D 2270	141
Flash point, open cup	°C	ASTM D 92	130
Pour point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% in weight	ASTM D 874	0.1

■ Hazard Identification

This product is not classified as toxic or hazardous under current legislation.

■ Handling

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

■ Health and safety hazards

Inhalation: Given that it is not a particularly volatile product, the risk of inhalation is minimal.

Ingestion: Do not induce vomiting. Supply water. Seek medical advice.

Contact with the skin: Wash thoroughly with soap and water.

Eyes: Wash thoroughly with water.

General measures: Seek medical advice.

■ Fire-extinguishing measures

No special measures required.

Fire-extinguishing measures: Foams, dry chemicals, CO₂, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

■ Environmental precautions

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

Decontamination and cleaning: Treat as an accidental oil spillage. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

repsolypf.com

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.