

MOTO SNOW 2T



SNOW

Lubricants

Description

Synthetic lubricant oil for 2-stroke snowmobiles. Its virtues include facilitating cold starts and it enables a better mix with petrol at low temperatures. It is without doubt the best way to obtain the best performance and to maintain exceptional engine protection in the most extreme weather conditions.

Properties

- Low pouring point, meaning it can be used in extremely cold temperatures.
- Suitable for snowmobiles with automatic oil injection or manual premix systems. The suggested ratio is between 2% and 4%. Adjust this ratio according to the manufacturer's recommendations and driving conditions. .
- Its detergency level prolongs engine life, keeps the exhaust vents clean and prevents the formation of deposits.
- Low smoke formula

Quality Level

- API TC

Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/mL	ASTM D 4052	0,881
Viscosity at 100 °C	cSt	ASTM D 445	10.15
Viscosity at 40 °C	cSt	ASTM D 445	77
Viscosity index	-	ASTM D 2270	141
Flash point, open cup	°C	ASTM D 92	122
Pour point	°C	ASTM D 97	-48
TBN	mg KOH/g	ASTM D 2896	5.5
Sulphated ashes	% in weight	ASTM D 874	0.18

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. October 2010.