

# MOTO SNOW

## 4T 0W30

SNOW



### Lubricants

#### Description

Synthetic lubricant oil for snow vehicles driven by 4-stroke engines and developed to meet the demands of the main manufacturers. It displays excellent behaviour at low temperatures thanks to its low viscosity; it enables the engine to develop maximum performance in intense cold or when there is snow, and it achieves perfect lubrication of the different engine elements in extreme environmental conditions.

#### Properties

- Low pour point, allowing its use under temperatures below zero.
- Its carefully researched viscosity provides a smooth flow at low temperatures, maintaining the lubricating film and the level of protection required for engines at these temperatures.
- Its modern formula endows this oil with magnificent antiwear, dispersant and antioxidant properties, preventing the formation of sludge and improving the engine's performance.

#### Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			0W30
Density at 15 °C	g/mL	ASTM D 4052	0.850
Viscosity at 100 °C	cSt	ASTM D 445	11.0
Viscosity at 40 °C	cSt	ASTM D 445	60
Viscosity at -35 °C	cP	ASTM D 5293	6200 max.
Viscosity index	-	ASTM D 2270	176
Flash point, open cup	°C	ASTM D 92	205 min.
Pour point	°C	ASTM D 97	-48 max.
TBN	mg KOH/g	ASTM D 2896	6.8
Sulphated ashes	% in weight	ASTM D 874	0.9
Bosch Injector Shearing: Viscosity at 100 °C after shear	cSt	CEC-L014-93	10.98

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. October 2010.