



# Nautico Gasoline Board 4T 10W40

## ■ Description

Lubricant oil developed for all types of outboard and outboard-inboard water-cooled 4-stroke petrol engines. Its composition provides excellent protection against corrosion and it is recommended by the majority of pleasure boat manufacturers. Its formula meets the strict NMMA FC-W standards for boat engines and ensures reliable sailing for the engine.

## ■ Properties

- Excellent antiwear properties which guarantee longer engine life.
- Good cold-flow which facilitates ignition and reduces engine wear.
- Avoids segment sticking by dispersing mud, varnishes and other high temperature oil oxidation products.
- Contains efficient antirust and anticorrosion inhibitors that protect the engine in the water.
- Avoids the appearance of mud, thanks to its dispersing additives. As a result, the engine and component cleanliness is optimal at all times.
- A highly stable alkaline reserve (TBN) gives great capacity to neutralise the acids formed in combustion.

## ■ Quality level

- NMMA FC-W

## ■ Technical Characteristics

	UNIT	METHOD	VALUE
SAE Grade			10W40
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.873
Viscosity at 100°C	cSt	ASTM D 445	15
Viscosity at 40°C	cSt	ASTM D 445	96
Viscosity at -25°C	cP	ASTM D 5293	7000 maximum
Viscosity rate	-	ASTM D 2270	155
Flash point, open cup	°C	ASTM D 92	190
T. B. N.	mg KOH/g	ASTM D 2896	7
Bosch Injector Shearing: Viscosity at 100°C after shear	cSt	CEC L014 93	12.83
Noack volatility, 1hr at 250°C	% in weight	CEC L 040 93	17.7

## ■ Hazard Identification

---

This product is not classified as toxic or hazardous under current legislation.

## ■ Handling

---

Minimum precautions should be taken to avoid prolonged contact with the skin. The use of gloves, visors or glasses is recommended to avoid splashes.

## ■ Health and safety hazards

---

**Inhalation:** Given that it is not a particularly volatile product, the risk of inhalation is minimal.

**Ingestion:** Do not induce vomiting. Supply water. Seek medical advice.

**Contact with the skin:** Wash thoroughly with soap and water.

**Eyes:** Wash thoroughly with water.

**General measures:** Seek medical advice.

## ■ Fire-extinguishing measures

---

No special measures required.

**Fire-extinguishing measures:** Foams, dry chemicals, CO<sub>2</sub>, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

## ■ Environmental precautions

---

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

**Decontamination and cleaning:** Treat as an accidental oil spillage. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

A safety information file is available on request.

repsolypf.com

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.